

HFC-35 High Flow, 3/8" 通徑

規格

- ✓工作壓力: 真空至125psi, 8.6 bar
- ✓使用溫度: -40°C至137.8°C
- ✓材質: 本體-Polysulfone
- ✓彈簧: 閥/扣門316不銹鋼
- ✓O-Ring: EPDM, 其它材質選用
- ✓顏色: 本體/白色, 扣門/灰色

應用例

- ✓精密過濾設備
- ✓製藥設備
- ✓設備的冷卻管路
- ✓食品及冷飲設備
- ✓生化製程管路
- ✓實驗及儀器裝置



3 可提供符合美國國家衛生基金會NSF C-2規範的接頭

快速接頭母座 Bodies

| 管內徑 | 編號 (直通) | 編號 (附閥) | 長度 |
|---------------------------------------|-----------------|------------------|-------|
| 外牙固定 Rigid Mount | | | |
| 3/8" NPT | HFC 10635 | HFCD 10635 | 2.73" |
| 1/2" NPT | HFC 10835 | HFCD 10835 | 2.88" |
| 3/4" NPT | HFC 101235 | HFCD 101235 | 3.12" |
| 3/8" BSPT | HFC 10635 BSPT | HFCD 10635 BSPT | 2.73" |
| 1/2" BSPT | HFC 10835 BSPT | HFCD 10835 BSPT | 2.88" |
| 3/4" BSPT | HFC 101235 BSPT | HFCD 101235 BSPT | 3.12" |
| 線上連接管鉤接頭 In Line Hose Barb | | | |
| 3/8" (9.5mm) ID | HFC 17635 | HFCD 17635 | 2.82" |
| 1/2" (12.7mm) ID | HFC 17835 | HFCD 17835 | 2.82" |
| 5/8" (15.9mm) ID | HFC 171035 | HFCD 171035 | 2.94" |
| 3/4" (19mm) ID | HFC 171235 | HFCD 171235 | 2.94" |
| 面板固定管鉤接頭 Panel Mount Hose Barb | | | |
| 3/8" (9.5mm) ID | HFC 16635 | HFCD 16635 | 2.82" |
| 1/2" (12.7mm) ID | HFC 16835 | HFCD 16835 | 2.82" |
| 5/8" (15.9mm) ID | HFC 161035 | HFCD 161035 | 2.94" |
| 3/4" (19mm) ID | HFC 161235 | HFCD 161235 | 2.94" |



◀ 面板固定孔直徑: 0.720"

◀ 面板厚度: 0.030"至 0.25"

◀ 面板固定孔墊片: EPDM

快速接頭插 Inserts

| 管內徑 | 編號 (直通) | 長度 | 編號 (附閥) | 長度 |
|-----------------------------|-----------------|-------|------------------|-------|
| 外牙固定 Rigid Mount | | | | |
| 3/8" NPT | HFC 24635 | 1.82" | HFCD 24635 | 1.94" |
| 1/2" NPT | HFC 24835 | 1.97" | HFCD 24835 | 2.09" |
| 3/4" NPT | HFC 241235 | 2.22" | HFCD 241235 | 2.34" |
| 3/8" BSPT | HFC 24635 BSPT | 1.97" | HFCD 24635 BSPT | 2.09" |
| 1/2" BSPT | HFC 24835 BSPT | 1.17" | HFCD 24835 BSPT | 2.09" |
| 3/4" BSPT | HFC 241235 BSPT | 2.21" | HFCD 241235 BSPT | 2.33" |
| 管鉤接頭 Hose Barb | | | | |
| 3/8" (9.5mm) ID | HFC 22635 | 1.91" | HFCD 22635 | 2.03" |
| 1/2" (12.7mm) ID | HFC 22835 | 1.91" | HFCD 22835 | 2.03" |
| 5/8" (15.9mm) ID | HFC 221035 | 2.03" | HFCD 221035 | 2.15" |
| 3/4" (19mm) ID | HFC 221235 | 2.03" | HFCD 221235 | 2.15" |
| 管鉤彎頭 Elbow Hose Barb | | | | |
| 3/8" (9.5mm) ID | HFC 23635 | 1.92" | HFCD 23635 | 2.04" |
| 1/2" (12.7mm) ID | HFC 23835 | 1.96" | HFCD 23835 | 2.16" |



HFC-57 High Flow, 3/8" 通徑

規格

- ✓工作壓力: 真空至125psi, 8.6 bar
- ✓使用溫度: -40°C至137.8°C
- ✓材質: 本體-抗紫外線Polysulfone
- ✓彈簧: 閥/扣門316不銹鋼
- ✓O-Ring: EPDM, 其它材質選用
- ✓顏色: 本體/扣門-黑色

應用例

- ✓農業噴霧設備
- ✓投幣販賣設備
- ✓化學品輸送管路
- ✓水處理設備
- ✓動力清洗設備
如灑水及洗街車

3 抗紫外線適合戶外使用

快速接頭母座 Bodies

| 管內徑 | 編號 (直通) | 編號 (附閥) | 長度 |
|---------------------------------------|-----------------|-------------------|-------|
| 外牙固定 Rigid Mount | | | |
| 1/2" NPT | HFC 10857 | HFC D 10857 | 2.88" |
| 1/2" BSPT | HFC 10857 BSPT | HFC D 10857 BSPT | 2.88" |
| 3/8" BSPT | HFC 10657 BSPT | HFC D 10657 BSPT | 2.73" |
| 3/4" BSPT | HFC 101257 BSPT | HFC D 101257 BSPT | 3.12" |
| 線上連接管鉤接頭 In Line Hose Barb | | | |
| 3/8" (9.5mm) ID | HFC 17657 | HFC D 17657 | 2.82" |
| 1/2" (12.7mm) ID | HFC 17857 | HFC D 17857 | 2.82" |
| 5/8" (15.9mm) ID | HFC 171057 | HFC D 171057 | 2.94" |
| 3/4" (19mm) ID | HFC 171257 | HFC D 171257 | 2.94" |
| 面板固定管鉤接頭 Panel Mount Hose Barb | | | |
| 3/8" (9.5mm) ID | | HFC D 16657 | 2.82" |
| 1/2" (12.7mm) ID | | HFC D 16857 | 2.82" |
| 5/8" (15.9mm) ID | | HFC D 161057 | 2.94" |
| 3/4" (19mm) ID | | HFC D 161257 | 2.94" |

◀ 面板固定孔直徑: 0.720"

◀ 面板厚度: 0.030"至 0.25"

◀ 面板固定孔墊片: EPDM

快速接頭插 Inserts

| 管內徑 | 編號 (直通) | 編號 (附閥) | 長度 |
|-------------------------|-----------------|-------------------|-------------|
| 外牙固定 Rigid Mount | | | |
| 1/2" NPT | HFC 24857 | HFC D 24857 | 1.95" |
| 1/2" BSPT | HFC 24857 BSPT | HFC D 24857 BSPT | 1.99"/2.06" |
| 3/4" NPT | HFC 241257 BSPT | HFC D 241257 BSPT | 2.19" |
| 3/8" BSPT | HFC 24657 BSPT | HFC D 24657 BSPT | 1.84"/1.91" |
| 管鉤接頭 Hose Barb | | | |
| 3/8" (9.5mm) ID | HFC 22657 | HFC D 22657 | 1.91"/2.03" |
| 1/2" (12.7mm) ID | HFC 22857 | HFC D 22857 | 1.91"/2.03" |
| 5/8" (15.9mm) ID | HFC 221057 | HFC D 221057 | 2.03"/2.15" |
| 3/4" (19mm) ID | HFC 221257 | HFC D 221257 | 2.03"/2.15" |



FFC-35 1/2" 通徑 大流量 Polysulfone 製

| 規格 | 應用例 | 材質 |
|--|---|--|
| <ul style="list-style-type: none"> ✓工作壓力:真空至125psi, 8.6 bar ✓連續使用溫度: -40°C至137.8°C | <ul style="list-style-type: none"> ✓精密過濾設備 ✓製藥設備 ✓設備的冷卻管路 ✓食品及冷飲設備 ✓生化製程管路 | <ul style="list-style-type: none"> ✓本體/扣門: Polysulfone ✓O-Ring: 食品級Buna-N ✓彈簧: 316不銹鋼 ✓顏色: 本體白色,扣門/黑灰色 ✓墊片: EPDM,其它材質選用 |



- 3 流量加倍外觀尺寸與 HFC 系列一樣
- 3 FFC 全系列採直通設計
- 3 可提供符合美國國家衛生基金會 NSF C-2 規範的接頭

快速接頭母座 Bodies

| 螺紋及管內徑 | 編號 (直通) | 長度 |
|---------------------------------------|-----------------|-------|
| 外牙固定 Rigid Mount | | |
| 1/2" NPT | FFC 10835 | 2.88" |
| 1/2" BSPT | FFC 10835 BSPT | 2.88" |
| 3/4" NPT | FFC 101235 | 3.12" |
| 3/4" BSPT | FFC 101235 BSPT | 3.12" |
| 線上連接管鉤接頭 In Line Hose Barb | | |
| 3/4" (19mm) | FFC 171235 | 2.94" |
| 面板固定管鉤接頭 Panel Mount Hose Barb | | |
| 3/4" (19mm) | FFC 161235 | 2.94" |



快速接頭插 Inserts

| 螺紋及管內徑 | 編號 (直通) | 長度 |
|-------------------------|-----------------|-------|
| 外牙固定 Rigid Mount | | |
| 1/2" NPT | FFC 24835 | 1.95" |
| 1/2" BSPT | FFC 24835 BSPT | 1.95" |
| 3/4" NPT | FFC 241235 | 2.14" |
| 3/4" BSPT | FFC 241235 BSPT | 2.14" |
| 管鉤接頭 Hose Barb | | |
| 3/4" (19mm) | FFC 221235 | 2.02" |



◀ 面板固定規格與 HFC 系列相同