

PP & PVC & PVDF Ball Valves 球阀

阀内不含金属材料

材质 Body: PVC (白色、灰色) & PP (白色、黑色) & PVDF (黑色)

O-ring/seal: Viton

耐压力: 0-125PSI

牙口: 1/8"~1/4"NPT 内牙 Female thread

1/8"~1/4"NPT 外牙 Male thread

插管: 1/8"~1/2" Barb (管钩)

快插: 1/4"~3/8"OD

迫紧: 1/8"~1/4" OD (带螺帽)



End Options

| | |
|------------------------------------|---|
| 1/8, 1/4 Male and Female NPT | 3/8 BIB (Smooth Barb) |
| 1/8, 1/4, 5/16, 3/8, 1/2 Hose Barb | 1/8, 1/4 JACO (Not NSF Standard 42 Certified) |
| 1/4, 3/8 SMC Push-To-Connect | |



Material Options

Gray PVC (Standard), White PVC, White Polypropylene, Black Polypropylene, Black Nylon, Black PVDF (Kynar®)

Seal Options

Buna-N, Ethylene Propylene, Fluoroelastomer (Viton®)

End Options

1/8, 1/4, 3/8 Male NPT
 1/4, 3/8, 1/2 Female NPT
 1/4, 3/8 SMC Push-To-Connect
 1/8, 1/4, 3/8, 1/2 Hose Barb
 Tapered Barb
 1/4, 3/8 JACO (Not NSF Standard 42 Certified)
 1/2 Female NPT with Stainless Support Ring

